

TDI

SPECIFICATION	
Apperance	clear liquid
APHA colour, max.	25
Sp. Gr. (at 20°C / 20°C)	1.22 ± 0.02
Purity (% by wt.), min.	99.7
Isomer Content (% by wt.)	
2,4 TDI	80 ± 1
2,6 TDI	20 ± 1
Total Acidity (ppm. by wt), max.	40
Hydrolyzable Chlorine (ppm.by wt.), max	80
Total Chlorine (ppm. by wt.) max.	700
CAS No.	584-84-9
UN No.	2078
Haz. Class	6.1
IMDG code page	6269

Uses

- Flexible polyurethane foam (moulded)
- Mattresses, Pillows & Quilts
- Furniture cushion
- Automobiles: Seats, Furniture, Lining, Sun visors etc...
- Padding & Lining: Garments, Shoes, Diaries, Carpets, Brief Cases, Bags, Purses etc.
- Acoustic Insulation
- Industrial Gaskets
- Protective pads for Sports & Medical use
- Industrial, Automobiles & Household Filters
- Paint Rollers
- Packing: Electronic items, Frozen Foods, Medicines, Audio-video Computer CD's
- Applicators: Shampoos, Wax, Shoe Polish, Household Chemicals
- Cleaning Tools for pipelines and tubes
- Miscellaneous: Toys, rakhi etc.
- Any type of cushioning
- C. A. S. E.
- Coating • Adhesives • Sealants • Elastomers

The material complies as per above specification

